



# Richpeace Automatic Perforation + Sewing + Embroidery machine






Model: RPCE-L-P+E+S-1-1200×800-B-P6+F9+IS2-VR1, VR2-LH50, AO-1P220

## Features

1. Richpeace new 3G computer control system, friendly HMI, flexible operation, large storage capacity, ensure highly precise running of the machine.
2. Six sizes round punching needle for perforation head: 0.8mm, 1.0mm, 1.2mm, 1.5mm, 2.0mm, 2.5mm, different sizes combination realize various pattern.
3. Servo motor driving for main shaft and frame driving, independent control.
4. Richpeace self-developed electrical and mechanics technology can meet customization requirements.
5. Bridge structure, stable frame, big sewing area, realizing any pattern design.
6. Equipped with automatic vacuum cleaner to remove the leather crumbs.
7. Automatic lubricating system, improves equipment service life and reduces manual maintenance.
8. 2X size of sewing rotary hook and 1X embroidery rotary hook, all are original from Japan.
9. Lifting sewing head could prevent frame collision and thread off.
10. Specialized multi-functional frame could satisfy different leather and synthetic leather processing.
11. Optional Richpeace PerSew CAD system, free design in sewing pattern and easy to realize the complicated and special processing integrated with embroidery, sewing, perforation together.

## Application

Applicable in field such as car seat covers, automotive interiors, furniture upholstery, sports shoes, leather shoes and leather garment....




## Models

Models	Working Area	Installation Area ( L×W× H)
RPCE-L-P+E+S-1-900×600-B-P6+F9+IS2-VR1, VR2-LH50, AO-1P220	900mm×600mm	4193mm×2100mm×1650mm
RPCE-L-P+E+S-1-1200×800-B-P6+F9+IS2-VR1, VR2-LH50, AO-1P220	1200mm×800mm	4793mm×2500mm×1650mm

## Parameters

Max. Sewing speed	1000rpm	Material Fixing	Leather Clamping Frame
Max. perforation speed	800rpm	Sewing Head Lift-stroke	50mm
Max. emb. speed	850rpm	Embroidery Trimming	Motorized
Stitch Length	0.1-12.7mm	Sewing Trimming	Pneumatic
Punching needle size	0.8mm, 1.0mm, 1.2mm, 1.5mm, 2.0mm, 2.5mm Round hole	Stitch type	Lock stitch
Sewing needle size	18#, 21#, 23#	Power supply	One phase 220V/50Hz
Emb. Needle size	11#	Power/Air pressure	5.5kW/0.6Mpa


## Main Configuration (Below are for reference, pls. consult with Richpeace for the final configurations)



Third generation electronic control system



Auto-Lubrication Device



Integrated leather frame



Servo motor



Industrial-grade powerful vacuum cleaner



Pattern code scanner ( optional)

## TIANJIN RICHPEACE AI CO., LIMITED

Add: No.6 Baozhong Road, Baodi Economic Development Area, Tianjin City, 301800 China  
 Email: sales@richpeace.com [www.richpeace.com](http://www.richpeace.com)

Tel: +86-22-22533456  
 Fax: +86-22-22530075

